

# Product Environmental Aspects Declaration



Facsimile ( PCR number: AH-03 )

No. AH-12-143  
Date of publication  
Oct./5/2012

**brother**  
at your side

<http://www.brother.co.jp/>

For inquiry:  
Environmental Product Group  
Environmental Management Dept.  
Brother Industries, Ltd.  
Tel: +81-52-824-2406  
FAX: +81-52-824-5667


## A3 Color Multi-Function Center MFC-J6510DW

### Specifications:

- Color Inkjet Printing
- Business Use
- Recording Paper Size: A3 (Max. 297 x 420mm)
- Original Sheet Size: Max-width 297mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing
- Product weight: 15.3 kg  
(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 4,050MJ
  - Global warming impact (CO<sub>2</sub> equivalent) 224.0kg
  - Acidification impact (SO<sub>2</sub> equivalent) 0.316kg



- Electric power consumption in 5 years of "Use stage" is 168kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

### Notes:

1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR:Product Category Rule. Visit EcoLeaf website under JEMAI homepage at [http://www.jemai.or.jp/ecoleaf\\_e/](http://www.jemai.or.jp/ecoleaf_e/) for details.
3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

### [Supplemental environmental information]

The product assembly and main parts of ink and inkjet head are produced at plants certified with ISO 14001.  
The product conforms to the International Energy Star Program.  
The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, September 29, 2004, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School  
Independent verification of the label and data, according to ISO 14025  internal  external Third party verifier \*: System auditor, Shozo Nakamura  
Program operator: Japan Environmental Management Association for Industry Email: [ecoleaf@jemai.or.jp](mailto:ecoleaf@jemai.or.jp)

\* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

## Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-12-143

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	Facsimile	Product type	MFC-J6510DW				
PCR code	AH-03	Product weight (kg)	15.32	Package (kg)	4.84	Weight total (kg)	20.16

In/Out items	Life Cycle Stage	Unit	Production		Distribution	Use	Disposal	Total										
			Raw material	Product														
<b>Energy Consumption</b>																		
Inventory analyses	Impact by Resource Consumption	Exhaustible resources	Energy resources	MJ	1.83E+03	1.91E+02	5.09E+01	1.96E+03	2.13E+01	4.05E+03								
				Mcal	4.37E+02	4.56E+01	1.22E+01	4.67E+02	5.09E+00	9.67E+02								
				kg	7.82E+00	1.24E+00	1.19E-04	9.78E+00	1.29E-01	1.90E+01								
				Inventory analyses	Impact by Resource Consumption	Exhaustible resources	Mineral resources	kg	1.85E+01	1.53E+00	1.11E+00	1.33E+01	2.26E-01	3.46E+01				
								kg	3.63E+00	6.22E-01	1.72E-02	5.40E+00	6.64E-02	9.73E+00				
								kg	3.36E-04	8.39E-05	8.06E-09	6.61E-04	8.72E-06	1.09E-03				
								kg	9.55E+00	0	0	2.97E+00	0	1.25E+01				
								kg	3.34E+00	0	0	6.68E-03	0	3.35E+00				
								kg	1.90E-01	0	0	0	0	1.90E-01				
								kg	2.77E-02	0	0	0	0	2.77E-02				
								kg	8.37E-03	0	0	3.24E-03	0	1.16E-02				
								kg	1.24E-02	0	0	4.38E-03	0	1.68E-02				
								kg	3.48E-02	0	0	5.57E-04	0	3.53E-02				
								kg	1.23E-02	0	0	0	0	1.23E-02				
								kg	-	-	-	-	-	-				
								kg	1.21E-01	0	0	0	0	1.21E-01				
								kg	-	-	-	-	-	-				
								kg	-	-	-	-	-	-				
								kg	-	-	-	-	-	-				
								kg	1.25E+00	0	0	4.30E-05	0	1.25E+00				
								kg	8.44E-01	1.94E-03	0	4.40E-03	6.21E-03	8.57E-01				
								kg	1.24E+00	1.26E-01	0	3.07E-01	1.82E-01	1.86E+00				
								kg	1.34E-01	0	0	0	0	1.34E-01				
								Inventory analyses	Impact by Emission/Discharge to the environment	to Atmosphere	Renewable resources	kg	1.00E+01	3.24E-02	0	2.76E+00	0	1.28E+01
												kg	8.58E+03	9.45E+02	8.97E-02	7.83E+03	1.09E+02	1.75E+04
												kg	9.01E+01	1.29E+01	3.61E+00	9.47E+01	1.95E+01	2.21E+02
												kg	5.15E-02	8.92E-03	2.32E-03	6.66E-02	1.02E-02	1.39E-01
												kg	1.24E-01	1.02E-02	1.92E-02	7.69E-02	2.18E-02	2.52E-01
												kg	8.76E-03	1.63E-04	5.77E-04	1.98E-03	2.77E-05	1.15E-02
												kg	8.98E-04	2.24E-04	2.15E-08	1.77E-03	2.34E-05	2.91E-03
												kg	1.01E-02	1.85E-03	5.42E-03	1.42E-02	3.95E-03	3.55E-02
												kg	1.75E-03	4.39E-04	4.22E-08	3.46E-03	4.58E-05	5.70E-03
												kg	4.10E-03	5.71E-05	5.48E-04	7.91E-04	7.25E-05	5.57E-03
kg	1.23E-02	3.22E-04	1.79E-03									4.36E-03	1.24E-03	2.00E-02				
kg	-	-	-									-	-	-				
kg	-	-	-									-	-	-				
kg	-	-	-	-	-	-												
kg	-	-	-	-	-	-												
kg	-	-	-	-	-	-												
kg	-	-	-	-	-	-												
kg	9.99E-01	5.69E-04	0	1.14E+00	7.77E+00	9.90E+00												
kg	1.32E+00	0	0	4.19E-03	0	1.33E+00												
kg	7.76E-03	0	0	0	0	7.76E-03												
kg	2.35E-04	5.86E-05	5.63E-09	4.61E-04	6.10E-06	7.60E-04												
Impact assessment	by Resource Consumption	Exhaustible resources	Energy resources (crude oil equivalent)	kg	3.06E+01	3.77E+00	1.13E+00					3.14E+01	4.60E-01	6.74E+01				
			Mineral resources (Iron ore equivalent)	kg	6.55E+01	0	0					4.19E+00	0	6.97E+01				
	Impact by Emission/Discharge to the environment	to Atmosphere	Global Warming (CO2 equivalent)	kg	9.24E+01	1.30E+01	3.77E+00					9.53E+01	1.95E+01	2.24E+02				
			Acidification (SO2 equivalent)	kg	1.38E-01	1.60E-02	1.58E-02					1.20E-01	2.55E-02	3.16E-01				

[Notes for readers: EcoLeaf common rules]

## I. Stage related

A. "Production" stage is intended for two sub-stages listed below.

- (1) "Raw material" production: consists of mining, transportation and raw material production.  
 (2) "Product" production: consists of the parts processing, assembly and installation.

B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage.

C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).

D. "Disposal" stage is intended for environmental impacts by product disposal.

## II. Inventory analyses

A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.

B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.

C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

## III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO<sub>2</sub> in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

## IV. Data entry format

A. Exponential notation, after the decimal point to two, should be used.

B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data).

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.

[Notes for readers: Target product specific]

1. Product weight includes ink cartridges, and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery.

2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of ink cartridges and an inkjet head, as well as the impact of product assembly.

3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.

The transportation distance in Japan uses 100 km as average distance.

4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48000 sheets and printing 48000 sheets by receiving.

This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days,

not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.

Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

## Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-12-143

PSC name	Facsimile(PCR ID:AH-03)	Product type	MFC-J6510DW				
LCA/LCIA in units of:	1	Product weight (kg)	15.32	Package (kg)	4.84	weight total (kg)	20.16

## 1. Product information (per unit): parts etc. by material and by process/assembly method

Product	Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly base Units (Parts B,C)			
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	2.91E+00	Paper	4.58E+00	Press molding: Iron (kg)	2.95E+00	Parts assembly (kg)	2.94E+00
	Stainless steel	5.26E-02	Semiconductor substrate	9.80E-01	Press molding: Nonferrous metal (kg)	3.42E-03		
	Aluminum	3.42E-03	Wood	0	Injection molding (kg)	9.99E+00		
	Other metal	0	Water	4.06E-02	Glass molding (kg)	1.30E+00		
	Thermoplastic resin	9.58E+00	Medium-sized motor	2.74E-01				
	Thermosetting resin	1.30E-02	Alkali-manganese dry battery	3.40E-02				
	Rubber	4.03E-01	Lubricants	1.95E-03				
	Glass	1.30E+00						
	Subtotal	1.43E+01	Subtotal	5.91E+00				
	Total	2.02E+01			Subtotal	1.43E+01	Subtotal	2.94E+00

Note : Nickel hydride battery has been calculated using the basic unit of Alkali-manganese dry battery.

## 2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

Consumption / Emission / Discharge	Classifier	Material	Material	Energy	Energy	Energy	Energy	Material	Energy
	Distribution	Corrugated cardboard (kg)	PP (kg)	Clean water (kg)	Furnace urban gas (13A) (m3)	Electricity (kwh)	Diesel truck: 4 ton (kg.km)	Clean water (kg)	Incineration: Industrial waste (kg)
Quantity	1.52E-02	2.13E-03	1.23E-01	2.65E-04	7.42E+00	1.85E+00	1.84E+00	8.66E-02	
Note									
Classifier	Energy	Energy	Material	Energy	Energy				
Distribution	Gasoline as fuel (kg)	Freight by air (kg.km)	Incineration: Industrial waste (kg)	Diesel truck: 10 ton (kg.km)	Freight by ship (kg.km)				
Quantity	3.77E-02	1.32E+02	1.86E+00	1.55E+01	1.41E+02				
Note									
Classifier									
Distribution									
Quantity									
Note									

Note

## 3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Diesel truck: 20 ton (kg.km)	Diesel truck: 20 ton (kg.km)	Diesel truck: 20 ton (kg.km)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)	Freight by ship (kg.km)
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg.km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg.km)
Quantity	2.02E+01	8.50E+01	3.08E+01	5.56E+03	2.02E+01	2.63E+03	1.00E+02	5.30E+04	
Note									
Means of transportation	Diesel truck: 10 ton (kg.km)	Diesel truck: 10 ton (kg.km)	Diesel truck: 10 ton (kg.km)	Diesel truck: 10 ton (kg.km)					
Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg.km)					
Quantity	2.02E+01	1.00E+02	3.08E+01	6.54E+03					
Note									

Note

## 4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

## 4.1 Product and accessories subject to this analysis

Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	PP (kg)	Incineration: Industrial waste (kg)	Stainless steel plate (kg)	Low density polyethylene (kg)
Quantity	1.68E+02	5.58E+02	2.24E+04	9.69E+02	9.23E-02	9.23E-02	2.05E-02	1.49E-01	
Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years			
Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Distribution	PP (kg)	POM(polyacetal) (kg)	ABS (kg)	PET (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	
Quantity	1.87E+00	4.71E-01	4.33E-01	2.72E-01	1.78E-02	2.11E-01	9.85E-01	2.34E-02	
Note									
Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Process	
Distribution	Clean water (kg)	Injection molding (kg)	Press molding: Iron (kg)	Electricity (kwh)	Urban gas (m3)	Gasoline as fuel (kg)	Clean water (kg)	Incineration: Industrial waste (kg)	
Quantity	1.76E+00	3.22E+00	2.05E-02	3.46E+00	1.15E-02	1.95E-02	5.33E+00	3.70E+00	
Note				Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	

Note Electric power consumption in 5 years of "Use stage" is 168kWh.

## 4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classifier	Consumption	Process	Process	Process				
	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill (as ash) (kg)	General waste (kg)	Landfill: General waste (kg)			
Quantity	4.58E+02	3.37E+00	4.70E+00	2.30E-02					
Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected					

Note

## 5. Disposition/Recycle stage information (per product): process method and scenarios

Scenario	Classifier	Consumption	Process	Process	Process				
	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill (as ash) (kg)	General waste (kg)	Landfill: General waste (kg)			
Quantity	1.92E+03	1.50E+01	1.43E+01	5.55E+00					
Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected					

Note

## 6. Others