

# Product Environmental Aspects Declaration



Interphone (PCR No.AX-03)

**Panasonic**

<http://panasonic.jp/door/>

Panasonic System Networks Co.,Ltd.  
 Communication Products Division  
 TEL:092-477-1821 FAX:092-477-1487  
 MAIL:ecoleaf@gg.jp.panasonic.com

**VL-SWN352KL**

Product Specification

- Personal use
- Hand free mutual telephone call
- With a camera function
- Main monitor station mass<sub>[catalogue]</sub> 0.81 kg
- Door station mass<sub>[catalogue]</sub> 0.18 kg
- Wireless monitor station mass<sub>[catalogue]</sub> 0.21 kg (Contain the Battery Pack)
- the intercom 1set, and the color monitor 1set and the wireless monitor 1set

**No. AX-09-025**


Date of publication  
 MAY 15, 2009



Life Cycle Impacts

	Total,all stage
Global warming(CO <sub>2</sub> equivalent)	108 kg
Acidification(SO <sub>2</sub> equivalent)	0.140 kg
Energy Consumption	2,280 MJ

Global warming Impact (CO<sub>2</sub> equivalent)



The manuals, accessories, packing material, and the set box are contained in the range of this declaration.  
 The environmental burden of use stage is calculated using assumption of seven years-usage and 30minutes/day-operation.

Notes:

1. Original LCA data is available on "PEIDS", Product Environmental Information Declaration Sheet, and "PDS",Product Data Sheet.
2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at [http://www.jemai.or.jp/ecoleaf\\_e/](http://www.jemai.or.jp/ecoleaf_e/) for details.
3. Although this product is manufactured in Vietnam, Japanese data have been used as EcoLeaf generic data, instead of Vietnam data that have not been developed.

**[Supplemental environmental information]**

Main assembly production of this is manufactured at the factory certified by ISO 14001.  
 Specific brominated flame retardants,PBB and PBDE are not obtained in plastic console material.  
 Pb-free solder is used for the main circuit board.  
 A chrome free steel plate which avoided hexavalent chromium is used for thos product.

PCR review was conducted by the chair Mr.Hisashi Ishitani, KEIO University at PCR Deliberation Committee in January 1, 2008.

Independent verification of the declaration and data, according to ISO14025:2006  internal  external  
 Third party verifier: name of the third party verifier \*was Mr.Keiichi Aramaki.

Programme operator: Japan Environmental Management Association for Industry, [ecoleaf@jemai.or.jp](mailto:ecoleaf@jemai.or.jp)

\* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

# Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Panasonic System Networks Co.,Ltd.
EcoLeaf registration no.	AX-09-025

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	Interphone		Product type	VL-SWN352KL			
PCR code	AX-03	Product weight (kg)	1.30	Package (kg)	1.36	Weight total (kg)	2.66

In/Out items	Life Cycle Stage	Unit	Production		Distribution	Use	Disposition	Total		
			Raw material	Product						
Energy Consumption			MJ	3.72E+02	9.32E+01	9.44E+00	1.80E+03	2.50E+00	2.28E+03	
			Mcal	8.88E+01	2.23E+01	2.25E+00	4.31E+02	5.97E-01	5.45E+02	
Inventory analyses	Impact by Resource Consumption	Energy resources	Coal	kg	1.75E+00	5.62E-01	2.20E-05	1.04E+01	1.17E-02	1.28E+01
			Crude oil (for fuel)	kg	4.41E+00	6.43E-01	2.06E-01	1.16E+01	3.28E-02	1.69E+01
			LNG	kg	8.10E-01	2.81E-01	3.18E-03	5.11E+00	6.20E-03	6.21E+00
			Uranium content of an ore	kg	9.76E-05	3.80E-05	1.49E-09	6.91E-04	7.91E-07	8.27E-04
			Crude oil (for material)	kg	8.01E-01	0	0	2.10E-02	0	8.22E-01
			Iron content of an ore	kg	2.18E-01	0	0	7.02E-02	0	2.88E-01
			Cu content of an ore	kg	7.03E-02	0	0	0	0	7.03E-02
			Al content of an ore	kg	8.04E-04	0	0	0	0	8.04E-04
			Ni content of an ore	kg	6.74E-03	0	0	1.44E-06	0	6.74E-03
			C content of an ore	kg	9.20E-03	0	0	2.61E-05	0	9.23E-03
		Mn content of an ore	kg	1.67E-02	0	0	7.20E-02	0	8.87E-02	
		Pb content of an ore	kg	6.79E-03	0	0	5.36E-03	0	1.21E-02	
		Sn content of an ore	kg	-	-	-	-	-	-	
		Zn content of an ore	kg	6.68E-02	0	0	5.28E-02	0	1.20E-01	
		Au content of an ore	kg	-	-	-	-	-	-	
		Ag content of an ore	kg	-	-	-	-	-	-	
		Silica Sand	kg	1.50E-01	0	0	1.28E-03	0	1.51E-01	
		Halite	kg	1.98E-01	0	0	1.70E-04	1.40E-03	1.99E-01	
		Limestone	kg	1.68E-01	0	0	1.66E-02	1.36E-02	1.98E-01	
		Natural soda ash	kg	1.32E-02	0	0	0	0	1.32E-02	
Wood	kg	2.34E+00	0	0	1.18E-01	0	2.46E+00			
Water	kg	2.52E+03	4.26E+02	1.67E-02	7.77E+03	9.74E+00	1.07E+04			
Impact by Emission/Discharge to the environment	to Atmosphere	CO2	kg	2.07E+01	4.39E+00	6.70E-01	8.02E+01	1.52E+00	1.07E+02	
		Sox	kg	1.34E-02	3.34E-03	3.99E-04	6.30E-02	8.30E-04	8.10E-02	
		Nox	kg	2.64E-02	2.70E-03	3.05E-03	5.00E-02	2.26E-03	8.45E-02	
		N2O	kg	1.75E-03	5.24E-05	1.14E-04	9.67E-04	3.76E-06	2.88E-03	
		CH4	kg	2.61E-04	1.02E-04	3.99E-09	1.85E-03	2.12E-06	2.21E-03	
		CO	kg	2.56E-03	6.52E-04	7.94E-04	1.23E-02	5.47E-04	1.68E-02	
		NM VOC	kg	5.10E-04	1.99E-04	7.82E-09	3.62E-03	4.15E-06	4.33E-03	
		CxHy	kg	7.80E-04	1.30E-05	9.52E-05	2.15E-04	1.85E-05	1.12E-03	
		Dust	kg	2.36E-03	1.50E-04	2.90E-04	2.84E-03	1.43E-04	5.78E-03	
		BOD	kg	-	-	-	-	-	-	
		COD	kg	-	-	-	-	-	-	
		N total	kg	-	-	-	-	-	-	
		P total	kg	-	-	-	-	-	-	
		SS	kg	-	-	-	-	-	-	
		Unspecified Solid Waste	kg	1.93E-01	6.87E-08	0	2.14E-01	1.76E+00	2.16E+00	
Slag	kg	2.87E-01	0	0	1.77E-01	0	4.64E-01			
Sludge	kg	1.72E-03	0	0	0	0	1.72E-03			
Low level radio-active waste	kg	6.84E-05	2.65E-05	1.04E-09	4.82E-04	5.53E-07	5.77E-04			
Impact assessment	by Res	Energy resources (crude oil equivalent)	kg	7.30E+00	1.65E+00	2.10E-01	3.01E+01	5.42E-02	3.93E+01	
		Mineral resources (Iron ore equivalent)	kg	2.96E+01	0	0	1.32E+01	0	4.27E+01	
		Global Warming (CO2 equivalent)	kg	2.11E+01	4.41E+00	7.01E-01	8.05E+01	1.52E+00	1.08E+02	
		Acidification (SO2 equivalent)	kg	3.19E-02	5.24E-03	2.54E-03	9.80E-02	2.41E-03	1.40E-01	
		Photochemical Oxidant	kg	1.49E-03	1.51E-04	1.56E-04	2.78E-03	6.81E-05	4.64E-03	

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
  - (1) "Raw material" production: consists of mining, transportation and raw material production.
  - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition" stage is intended for environmental impacts by product disposition.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data).  
(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)(Refer to the list of Basic Unit at Ecoleaf website.)

[Notes for readers: Target product specific]

As a general rule, the generic data of materials are numerical data of material production from ores and do not include scraps.

## Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03s-02
Product vendor	Panasonic System Networks Co.,Ltd.
EcoLEaf registration no.	AX-09-025

PCR name	Interphone (PCR-ID: AX-03)	Product type	VL-SWN352KL				
LCA/LCIA in units of:	1 set	Product weight (kg)	1.30	Package (kg)	1.36	Weight total (kg)	2.66

### 1. Product information (per unit): parts etc. by material and by process/assembly method

Product	Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)			
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	5.67E-02	Paper	1.07E+00	Press molding:Iron (kg)	3.15E-01		
Electromagnetic steel plate	1.32E-01	Assembled circuit board	3.13E-01	Press molding: Nonferrous metal (kg)	7.16E-01			
Stainless steel	4.26E-02	Battery	4.50E-02	Injection molding (kg)	9.93E-01			
Copper	8.98E-02							
Aluminum	7.60E-04							
Glass	6.47E-02							
Thermoplastic resin	8.09E-01							
Rubber	3.08E-02							
Subtotal	1.23E+00	Subtotal	1.43E+00					
Total			2.66E+00	Subtotal	2.02E+00	Subtotal	0.00E+00	

Note Intercom, wireless monitor and color monitor are calculated in product weight.  
Accessories, such as packing material and a handling description, are calculated for package weight.

### 2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

Consumption	Classification	Energy	Energy	Energy	Material	Material	Consumption	Consumption
	Distribution	Electricity (kWh)	Gasoline (kg)	LPG (kg)	Industrial water (kg)	Clean water (kg)	Diesel truck: 4 ton (kg.km)	Freight by ship (kg.km)
	Quantity	7.67E+00	2.95E-04	1.71E-05	1.26E-03	1.29E-03	7.74E+00	4.38E+02
	Note							
Emission/Discharge	Classification							
	Distribution							
	Quantity							
	Note							

Note The manufacturing stage consists of assembly of a LCD unit, a speaker unit and final assembly of main unit.  
Industrial water is used as the cooling water.

### 3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Consumption	Consumption	Consumption	Consumption
	Conditions	Diesel oil as fuel (kg)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Diesel truck: 4 ton (kg.km)
	Quantity	9.80E-03	9.90E+03	6.85E+02	6.61E+02
	Note				

Note The land transportation from overseas manufacturing site to Japan and marine transportation load are added up.  
Moreover, domestic transportation distance is set to 500km.

### 4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

#### 4.1 Product and accessories subject to this analysis

Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	Diesel truck: 10 ton (kg.km)	Diesel truck: 4 ton (kg.km)	Electricity (kWh)	Alkaline-Manganese dry battery (kg)	Paper (Western style) (kg)	PET (kg)	Corrugated cardboard (kg)
	Quantity	1.64E+02	1.34E+00	1.90E+02	1.41E-01	4.37E-02	3.17E-02	8.33E-03
	Note							

Note Based on the PCR, usable period is 7 years and operating time is 30 minute / day.  
Excepting the operating time, the product is in standby mode all day.

#### 4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classification	Consumption	Discharge	Discharge
	Distribution	Shredding (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)
	Quantity	2.80E-01	8.00E-02	2.00E-01
	Note			

Note Disposed affect of batteries consumed are added up in 7 years.

### 5. Disposition/Recycle stage information (per product): process method and scenarios

Scenario	Classification	Consumption	Consumption	Discharge	Discharge
	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill (as ash) (kg)	Landfill: General waste (kg)
	Quantity	5.32E+02	2.66E+00	1.07E+00	1.59E+00
	Note				

Note As wastes, combustibles are added up after crush and incineration and incombustibles are added up as reclamation.

### 6. Others