

Product Environmental Aspects Declaration



Flat-bed / Sheet-fed scanner (PCR-ID: CA-01)

No. CA-13-015

Date of publication

August/9/2013

ScanSnap SV600



<http://www.fujitsu.com/>
FUJITSU LIMITED

<http://www.pfu.fujitsu.com/>
PFU LIMITED

* ScanSnap Contact:
<http://scansnap.fujitsu.com/>


PFU LIMITED
Imaging Service & Support center
E-mail : scanners@pfu.fujitsu.com



Product Name	ScanSnap SV600
Product Category	Flat-bed scanner (Without ADF) For Personal and Business
Scanning Speed	Simplex, 3sec/paper
Scanning Size	432m X 300mm
Output Resolution	600 X 600 dpi (dots per inch)
Scanning Method	Color CCD (Charge coupled device) Image Sensor: CCD X 1

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO ₂ equivalent)	39.2kg (37.4kg)
Acidification (SO ₂ equivalent)	0.07kg (0.066kg)
Energy resources (crude oil equivalent)	673MJ (637MJ)

※Figures in () indicated environmental impact including recycle effect *note3



The burdens have been calculated with 20 scans per day, a monthly use of 4 days, and 5 years of use, for the number of scans of 480 times (4,800 pages) overall.

Notes:

1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at <http://www.ecoleaf-jemai.jp/eng/> for details.
3. Recycle Effect illustrates an indirect influence to other products/services.
4. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.

[Supplemental environmental information]

- Certified regulations: Energy Star Version 1.2
- This product are produced in our factories certified to ISO14001 management system standard.
- Conformance with RoHS Directive (2011/65/EU)

PCR review was conducted by : PCR Deliberation Committee, June 07, 2006, Name of representative: Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025:2006 internal external

Third party verifier: Eikyu Watanabe*

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02Bs-02
Product vendor	PFU LIMITED
EcoLeaf registration no.	CA-13-015

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	Flat-bed / Sheet-fed scanner		Product type	ScanSnap SV600			
PCR code	CA-01	Product weight (kg)	2.7	Package (kg)	2.2	Weight total (kg)	4.9

In/Out items	Life Cycle Stage	Unit	Production		Distribution	Use	Disposition	Recycle Effect			
			Raw material	Product							
Energy Consumption			MJ	5.02E+02	3.61E+01	2.15E+01	1.10E+02	2.68E+00	-3.55E+01		
			Mcal	1.20E+02	8.61E+00	5.14E+00	2.63E+01	6.41E-01	-8.47E+00		
Inventory analyses	Impact by Resource Consumption	Energy resources	Coal	kg	3.25E+00	2.55E-01	5.03E-05	6.27E-01	1.58E-02	-1.70E-01	
			Crude oil (for fuel)	kg	5.32E+00	2.95E-01	4.70E-01	7.09E-01	2.92E-02	-4.03E-01	
			LNG	kg	1.01E+00	1.27E-01	7.26E-03	3.14E-01	8.14E-03	-2.53E-02	
			Uranium content of an ore	kg	1.07E-04	1.72E-05	3.41E-09	4.25E-05	1.07E-06	-7.83E-07	
			Crude oil (for material)	kg	1.41E+00	0	0	0	0	-2.32E-01	
			Iron content of an ore	kg	1.48E+00	0	0	0	0	-1.45E-01	
			Cu content of an ore	kg	1.08E-01	0	0	0	0	-5.70E-03	
			Al content of an ore	kg	1.69E-01	0	0	0	0	-1.64E-02	
			Ni content of an ore	kg	4.64E-03	0	0	0	0	-2.96E-06	
			C content of an ore	kg	6.78E-03	0	0	0	0	-5.40E-05	
			Mn content of an ore	kg	8.34E-03	0	0	0	0	-1.26E-04	
			Pb content of an ore	kg	7.99E-03	0	0	0	0	-4.63E-04	
			Sn content of an ore	kg	0	0	0	0	0	0	
			Zn content of an ore	kg	7.85E-02	0	0	0	0	-4.55E-03	
			Au content of an ore	kg	0	0	0	0	0	0	
			Ag content of an ore	kg	0	0	0	0	0	0	
			Silica Sand	kg	1.15E-01	0	0	0	0	-2.45E-02	
			Halite	kg	7.68E-01	0	0	0	1.69E-03	-8.13E-03	
			Limestone	kg	3.93E-01	0	0	0	1.89E-02	-3.15E-02	
			Natural soda ash	kg	7.92E-03	0	0	0	0	-2.53E-03	
			Renewable resources	Wood	kg	2.75E+00	0	0	0	0	-1.34E+00
				Water	kg	2.94E+03	1.98E+02	3.80E-02	4.75E+02	1.32E+01	-8.82E+01
			Impact by Emission/Discharge to the environment	to Atmosphere	CO2	kg	2.80E+01	2.00E+00	1.52E+00	4.88E+00	2.06E+00
Sox	kg	2.19E-02			1.52E-03	1.28E-03	3.72E-03	1.09E-03	-1.15E-03		
Nox	kg	3.66E-02			1.22E-03	1.33E-02	2.95E-03	2.37E-03	-3.34E-03		
N2O	kg	2.39E-03			2.66E-05	1.70E-04	5.33E-05	4.10E-06	-1.94E-04		
CH4	kg	2.84E-04			4.60E-05	9.11E-09	1.14E-04	2.86E-06	-1.80E-06		
CO	kg	4.39E-03			2.97E-04	4.69E-03	7.21E-04	4.45E-04	-2.49E-04		
NMVOG	kg	5.55E-04			9.02E-05	1.79E-08	2.22E-04	5.60E-06	-3.51E-06		
CxHy	kg	1.09E-03			7.82E-06	3.13E-04	1.16E-05	1.00E-05	-9.21E-05		
Dust	kg	3.63E-03			6.49E-05	1.14E-03	1.59E-04	1.37E-04	-2.73E-04		
BOD	kg	-			-	-	-	-	-		
COD	kg	-			-	-	-	-	-		
N total	kg	-			-	-	-	-	-		
P total	kg	-			-	-	-	-	-		
SS	kg	-			-	-	-	-	-		
to Soil system	Unspecified Solid Waste	kg			2.35E-01	1.96E-04	0	0	2.12E+00	4.45E-01	
	Slag	kg	6.95E-01	0	0	0	0	-4.91E-02			
	Sludge	kg	3.53E-01	0	0	0	0	-3.53E-02			
	Low level radio-active waste	kg	7.52E-05	1.20E-05	2.38E-09	2.96E-05	7.46E-07	-5.46E-07			
Impact assessment by Emission/Discharge to environment	to Atmosphere	Energy resources (crude oil equivalent)	kg	9.50E+00	7.53E-01	4.79E-01	1.84E+00	5.79E-02	-5.48E-01		
		Mineral resources (Iron ore equivalent)	kg	3.69E+01	0	0	0	0	-2.02E+00		
		Global Warming (CO2 equivalent)	kg	2.87E+01	2.01E+00	1.57E+00	4.89E+00	2.06E+00	-1.86E+00		
		Acidification (SO2 equivalent)	kg	4.75E-02	2.37E-03	1.06E-02	5.79E-03	2.75E-03	-3.49E-03		
		Photochemical Oxidant	kg	2.15E-03	6.78E-05	5.91E-04	1.64E-04	6.30E-05	-1.50E-04		
to Water system	-	-	-	-	-	-	-				

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 (1) "Raw material" production: consists of mining, transportation and raw material production.
 (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling (e.g. impact reduction of raw material production).
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of used products to other businesses for material reclaim/parts reuse.
 Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease by volume reduction of used materials/parts.
 Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts reclaiming process, and decrease by volume reduction of new materials/parts production.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
 B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
 C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
 B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV. Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
 B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
 C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
 (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. Regarding the "Raw material" production, the environmental burdens of resource mining, transportation and raw material production for the main unit, accessories and packaging materials are calculated using the EcoLeaf basic unit.
2. In "Product" production, for parts processing, the environmental burden is calculated using the EcoLeaf basic unit and production site data.
For Parts/material C assembled at other than the main unit assembly site, the burden is calculated using the EcoLeaf basic unit (Assembly).
3. The "Distribution" stage basic conditions and basic unit are in accordance with the provisions of PCR.
The burdens are calculated with 500km for the total domestic transportation distance.
For transportation from China, the burdens of transporting by truck and sea are entered into the calculation.
4. The "Use" stage basic conditions and basic unit are in accordance with the provisions of PCR.
The burden of electricity consumption is calculated with the total scanning number of 4,800 sheets in the customer use period of 5 years.
The electricity consumption during power-off is entered into the calculation, presuming that the products remain plugged even if not in use.
5. At the "Disposition/Recycle" stage, in accordance with the provisions of PCR, the recycling scenario is established at our company.
The recycling burden is calculated with the 10% product recovery rate from the customer.
For the 90% non-recovery rate, the burden is calculated by using the General Waste Disposal Scenario.
For manuals, packaging boxes and cushioning materials, the recycling burden is calculated by setting up the Open Recycling Scenario.
6. Regarding "Recycle Effect", the burdens accompanying the production of raw materials using the materials recycled from the parts are deducted.

Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03s-02
Product vendor	PFU LIMITED
EcoLEaf registration no.	CA-13-015

PCR name	Flat-bed / Sheet-fed scanner (PCR-ID: CA-01)	Product type	ScanSnap SV600				
LCA/LCIA in units of:	1 unit	Product weight (kg)	2.7	Package (kg)	2.2	Weight total (kg)	4.9

1. Product information (per unit): parts etc. by material and by process/assembly method

Product	Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)			
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Other metals	1.89E-01	Rubber	7.77E-02	Press molding:iron (kg)	1.39E+00	Parts assembly (kg)	5.28E-01
	Ordinary steel	1.37E+00	Paper	1.28E+00	Press molding:Nonferrous metal (kg)	4.37E-01		
	Stainless steel	2.92E-02			Injection molding (kg)	1.51E+00		
	Semiconductor circuit board	3.01E-01			Glass molding (kg)	8.65E-03		
	Thermoplastic resin	1.45E+00						
	Aluminium	1.55E-01						
	Medium-sized motor	4.73E-02						
	Glass	5.56E-03						
	Subtotal	3.54E+00	Subtotal	1.36E+00				
	Total	4.91E+00	Subtotal	3.34E+00	Subtotal	5.28E-01		

Note The environmental burdens of the main unit, accessories and packaging materials are included.

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

Consumption	Classification	Energy	Energy	Material				
	Distribution	Electricity (kWh)	Diesel oil as fuel (kg)	Industrial water (kg)				
	Quantity	4.73E-01	7.18E-03	5.20E+00				
	Note							
Emission/Discharge	Classification							
	Distribution							
	Quantity							
	Note							

Note The burdens of mounting parts on printed circuit boards, air conditioners, electric lights, electric tools and test equipment at the product production site are included.

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)	Freight by ship (kg·km)
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
	Quantity	4.91E+00	9.00E+01	3.27E+01	1.35E+03	4.91E+00	3.00E+03	1.00E+02	1.47E+04
	Note	Transport in China				Transport from China to Japan			
Distribution	Means of transportation	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Diesel truck: 10 ton (kg·km)	Diesel truck: 4 ton (kg·km)	Diesel truck: 4 ton (kg·km)	Diesel truck: 4 ton (kg·km)	Diesel truck: 4 ton (kg·km)
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
	Quantity	4.91E+00	2.20E+01	3.27E+01	3.30E+02	4.91E+00	5.00E+02	4.09E+01	6.00E+03
	Note	Transport from the harbor to the warehouse				Transport from the warehouse to customer			

Note In accordance with the provisions of PCR, the burdens are calculated with 500km for the total domestic transportation distance. For transportation from China, the burdens of transporting by truck and sea are entered into the calculation.

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

Product	Classification	Consumption						
	Distribution	Electricity (kWh)						
	Quantity	1.17E+01						
	Note							

Note In accordance with the provisions of PCR, the burdens of electricity consumption and transportation are calculated with the total scanning number of 4,800 sheets in the customer use period of 5 years.

The electricity consumption during power-off is entered into the calculation, presuming that the products remain plugged even if not in use.

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classification							
	Distribution							
	Quantity							
	Note							

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

Scenario	Classification	Process	Process	Process	Consumption	Consumption	Process	Deduction	Process
	Distribution	Shredding (kg)	Landfill: General waste (kg)	Incineration to landfill (as ash) (kg)	Electricity (kWh)	Diesel oil as fuel (kg)	Recycle: to cold-rolled steel (kg)	Cold-Rolled steel plate (kg)	Recycle: to copper plate (kg)
	Quantity	4.60E+00	1.89E+00	1.49E+00	9.37E-02	3.10E-04	1.40E-01	1.40E-01	1.89E-02
	Note								
	Classification	Deduction	Process	Deduction	Process	Deduction	Process	Deduction	Process
	Distribution	Copper plate (kg)	Recycle: to Aluminum plate (kg)	Aluminum plate (kg)	Recycle: to Glass (kg)	Glass (kg)	Recycle: to Thermoplastic pellet (kg)	ABS (kg)	Sorting: Nonferrous metal(by eddy current with wind force) (kg)
	Quantity	1.89E-02	1.55E-02	1.55E-02	3.01E-02	3.01E-02	2.31E-01	8.70E-02	9.99E-01
	Note								
	Classification	Process	Deduction	Process	Deduction	Process	Condition	Condition	Condition
	Distribution	Recycle: to corrugated cardboard (kg)	Corrugated cardboard (kg)	Sorting: Plastics (by relative density difference in water) (kg)	Polystyrene (kg)	Landfill: Industrial waste (kg)	Diesel truck: 2 ton (kg · km)	Diesel truck: 2 ton (kg · km)	Diesel truck: 2 ton (kg · km)
	Quantity	6.29E-01	6.29E-01	2.25E-01	1.44E-01	4.65E-01	5.27E+01	8.61E+01	1.94E+01
	Note								

Note Based on the recycling scenario established at our company, the recycling burden is calculated with the 10% product recovery rate from the customer.
For the 90% non-recovery rate, the burden is calculated by using the General Waste Disposal Scenario.
For manuals, packaging boxes and cushioning materials, the recycling burden is calculated by setting up the Open Recycling Scenario.

6. Others

Regarding "Recycle Effect", the burdens accompanying the production of raw materials using the materials recycled from the parts are deducted.