Product Environmental Aspects Declaration

Heat-resistant crystallized glass for fire door (intermediate goods) (Applicable PCR No. DP-01-02)



No. DP-18-002 Date of publication November 12, 2018

Nippon Electric Glass

http://www.neg.co.jp/

Contact information Nippon Electric Glass Co., Ltd. Consumer Glass Division Quality assurance department TEL:+81-0749-85-5909 FAX:+81-0749-85-4059

FIRELITE PLUS

Name of product: Heat resistant crystallized glass for fire door (laminated glass)


Product specifications: Heat-proof temperature:

800 °C Sash not included Calculated weight: 1 kg

Certification: fire protection equipment, specific fire protection equipment certification, UL certification

Consumption and discharge in a life cycle	All the stage sum totals
Global Warming (CO ₂ equivalent)	4.26kg
Acidification (SO ₂ equivalent)	4.47g
Energy Consumption	78.0MJ





This product is an intermediate goods.

Distribution, use, disposal and recycling are not covered.

Notes

- 1. The basic data is described on the product environmental information disclosure sheet (PEIDS) and product data sheet.
- 2. For unified standards for data calculation, please refer to product classification standard (PCR). Please visit http://www.ecoleaf-jemai.jp/ for details.
- 3. The country of shipment of this product is Japan, and it is calculated using data in Japan. Part of the basic unit data is using IDEA Ver 2.0.
- 4. It is calculated using the characterization coefficient v 02.1 of the Eco Leaf program.

[Supplemental environmental information]


We manufacture it at a business site that has received ISO 14001 certification.(Head office site, Takatsuki site) Arsenic is not contained in this product.

PCR review was conducted by :September 1st .2016: Yuko Yamaguchi Affiliation Kyoritsu Women's Junior College Independent verification of the declaration and data, according to ISO14025 ISO21930 □internal ■external Third party verifier: Yasuo Koseki

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

^{*} In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are wri

Product Environmental Information Data Sheet (PEIDS)





PCR name	Fire-rated glass ceramics (inter	mediate product)	Product type	firelite plus			
PCR code	DP-01-02	Product weight (kg)	1	Package (kg)	0	Weight total (kg)	1

				Life Cycle Stage		Produ	uction				
In/Ou	ut iten	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Total
		_			MJ	2.33E+01	5.51E+01	0	0	0	7.84E+01
		Er	nergy C	Consumption	Mcal	5.57E+00	1.32E+01	0	0	0	1.87E+01
			8	Coal	kg	1.05E-01	1.65E-01	0	0	0	2.71E-01
			onic	Crude oil (for fuel)	kg	1.88E-02	3.07E-01	0	0	0	3.25E-01
			<u>ş</u>	LNG	kg	6.01E-02	4.66E-01	0	0	0	5.26E-01
			inerç	Uranium content of an ore	kg	1.12E-06	1.12E-05	Ö	0	Ö	1.23E-05
	_			Crude oil (for material)	kg	2.63E-01	4.75E-04	0	0	0	2.64E-01
	Consumption			Iron content of an ore	kg	7.63E-05	4.74E-08	0	0	0	7.63E-05
	du	ses		Cu content of an ore	kg	2.01E-07	1.12E-10	0	0	0	2.01E-07
	ıπ	l E		Al content of an ore	kg	4.93E-01	3.66E-03	0	0	0	4.96E-01
	Suc	SO	"	Ni content of an ore	kg	5.81E-07	4.02E-10	0	0	0	5.81E-07
	ŏ	ē	ĕ	C content of an ore	kg	1.39E-06	1.13E-09	0	0	0	1.39E-06
	g	Exhaustible resources	in in	Mn content of an ore	kg	8.31E-07	5.25E-10	0	0	0	8.32E-07
	'n	딅	980	Pb content of an ore	kg	1.80E-06	1.06E-09	Ö	0	0	1.80E-06
	SO	sng	ā	Sn content of an ore	kg	1.001-00	1.002-03	-	-	-	1.00L-00
	Impact by Resource	Å	Mineral resources	Zn content of an ore	kg	7.38E-08	2.75E-11	0	0	0	7.38E-08
	>	ш		Au content of an ore	kg	1.48E-10	8.62E-14	0	0	0	1.49E-10
	it k			Ag content of an ore	kg	3.44E-09	1.16E-12	0	0	0	3.44E-09
	рас			Silica Sand	kg	4.38E-01	1.42E-10	0	0	0	4.38E-01
SS	ш			Halite	kg	1.06E-02	6.46E-05	0	0	0	1.07E-02
analyses	_			Limestone	kg	2.06E-01	8.22E-05	0	0	0	2.06E-01
<u> </u>				Natural soda ash	kg	4.11E-03	0	0	0	0	4.11E-03
ਕ			0	Wood		4.11L-03	U	-	-	-	4.11L-03
<u> </u>		anew Fish	es es	Water	kg	2.77E+02	1.39E+02	0	0	0	4.16E+02
ı te		ž	ē		kg	1.19E+00	2.66E+00	0	0	0	
Inventory	en	Emission/Discharge to the environment		CO2	kg	7.28E-04	1.11E-03	0	0	0	3.85E+00 1.84E-03
드	שר		<u>e</u>	Sox	kg	7.26E-04 7.05E-04	3.05E-03	0	0	0	3.75E-03
	io		Atmosphere	Nox N2O	kg	6.17E-05	1.37E-03	0	0	0	3.75E-03 1.44E-03
	Ž		Sp		kg			0	0	0	
	9 6		2	CH4 CO	kg	1.03E-03	3.16E-05	0	0	0	1.06E-03
	the		₹		kg	6.03E-05	4.35E-04	0		0	4.95E-04
	to		2	NMVOC	kg	1.28E-05	5.85E-05	0	0	0	7.13E-05
	ge		_	СхНу	kg	1.33E-05	2.40E-04				2.54E-04
	Jar			Dust	kg	5.55E-04	1.18E-04	0	0	0	6.74E-04
	sch	Water system	domain	BOD	kg	1.57E-06	6.65E-09	0	0	0	1.58E-06
	Ö	sys	do	COD	kg	3.66E-06	1.61E-08	0	0	0	3.68E-06
	on/	ater	Water	N total	kg	1.10E-07	8.43E-11	0	0	0	1.10E-07
	ssi	Š	Š	P total	kg	2.31E-13	1.82E-16	0	0	0	2.31E-13
	E.	\$	- p	SS	kg	3.23E-06	1.42E-08	0	0	0	3.25E-06
			em	Unspecified Solid Waste	kg	5.34E-02	2.93E-03	0	0	0	5.63E-02
	by .		Soil system	Slag	kg	1.66E-07	1.28E-10	0	0	0	1.66E-07
	act		ie S	Sludge	kg	8.54E-02	3.79E-04	0	0	0	8.58E-02
	Impact		ο̈	Low level radio-active waste	kg	1.60E-04	7.91E-06	0	0	0	1.67E-04
			5	Hazardous waste	kg	0.00E+00	1.19E-03	0	0	0	1.19E-03
ent	by Res	haus	resourc es	Energy resources (crude oil equivalent)	kg	1.68E-01	1.07E+00	0	0	0	1.24E+00
SI	~ ~	Щ.	res	Mineral resources (Iron ore equivalent)	kg	1.24E+00	8.41E-03	0	0	0	1.25E+00
es	- 0.		here	Global Warming (CO2 equivalent)	kg	1.23E+00	3.03E+00	0	0	0	4.26E+00
assessment	by Emission / Discharge to environment		to Atmosph	Acidification (SO2 equivalent)	kg	1.22E-03	3.24E-03	0	0	0	4.47E-03
ct	Emis char iron		Atm	Ozone Depletion (CFC-11 equivalent)	kg	-	-	-	-	-	
Impact	by b Dis.			Photochemical Oxidant	kg	2.48E-04	1.64E-04	0	0	0	4.13E-04
≟	T to ∧ as		sy sy m	Eutrophication (Phosphate equivalent)	kg	1.27E-07	3.90E-10	0	0	0	1.27E-07

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition" stage is intended for environmental impacts by product disposition.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore,
- B. Data on energy resources are presented based on origin in calorific value, e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO₂ in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

 C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes " " item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

Product data sheet

(Input data and parameters for LCA)

	(input data and parameters for Eer t)
Document control no.	F-03s-02
Product vendor	Nippon Electric Glass Co. , Ltd.
EcoLEaf registration no.	DP-18-002



PCR name	Fire-rated glass ceramics (intermediate product)	Product type	firelite plus				
LCA/LCIA in units of:	1kg	Product weight (kg)	1	Package (kg)	0	Weight total (kg)	1

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bre	eakdown of pi	rimary materials		Math breakdown of parts, whi	ch need to apply	Processing / Assembly Base Ur	nits (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Silica sand				Blow molding (kg)	3.90E-02		
	Aluminum oxide	5.60E-01						
ಕ	Lithium carbonate							
ੂ ਜ਼ੁ	glass	4.90E-02						
2	Reproduction	3.52E-01						
۵.	synthetic resin	3.90E-02						
	Subtotal	1.00E+00	Subtotal	0.00E+00				
		Total		1.00E+00	Subtotal	3.90E-02	Subtotal	0.00E+00

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

	Classification	Energy	Energy	Material	Energy	Material	Energy	Material	Material
	Distribution	Diesel oil as fuel (kg)	Electricity (kWh)	Ultrapure water (kg)	Furnace urban gas (13A) (m3)	Industrial water (kg)	Furnace LNG (kg)	Alumina	Diesel truck:10 ton (kg·km)
Consumption	Quantity	3.00E-03	3.00E+00	1.00E+00	4.86E-01	1.20E+01	9.15E-05	1.00E-03	7.74E+01
	Note								
Inst	Classification	Material							
S	Distribution	Freight by ship (kg·km)							
	Quantity	4.32E+03							
	Note								
arge	Classification	Water system	Soil system	Soil system					
/Disch	Distribution	Sewage processing (kg)	Unspecified Solid Waste	Landfill:General waste (kg)					
sion,	Quantity	1.10E+01	1.19E-03	1.00E-03					
Emis	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

<u> </u>	Plantation stage intermation (per anny), means, aletanes, leading rate, senioring and sinice end discontinuous											
Distribution	Means of transportation											
	Conditions											
	Quantity											
	Note											

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification				
duct	Distribution				
Proc	Quantity				
	Note				

Note

4.2 Disposition/Recycle information on consumables and replacement parts

1 ~	Classification	-	-	-		
	Distribution					
l su	Quantity					
S	Note					

Note

5. Disposition/Recycle stage information (per product); process method and scenarios

. Dispe	Disposition/Recycle stage information (per product): process method and scenarios											
Scenario	Classification											
	Distribution											
	Quantity											
	Note											

Note

6. Others